

OAX4010 automotive ISP product brief



available in
a lead-free
package

Automotive Image Signal Processor Featuring Industry's Leading LED Flicker Mitigation and HDR Over Automotive Temperature Range

OmniVision's OAX4010 automotive image signal processor (ISP) features the new HDR and LFM Engine (HALE) combination algorithm. The On-Chip LFM and HDR solution uses a proprietary method to simultaneously provide 120 dB HDR and industry's leading LFM for automotive viewing systems, giving drivers a better picture of their surroundings. When the OAX4010 is paired with OmniVision's OX01A10 and OX02A10, this combination offers the most compact solution in the industry for the smallest possible camera footprint. The OAX4010 can process the images from one camera at 60 fps or two cameras at 30 fps, which reduces the number of ISPs required for surround-view system (SVS) cameras by 50%.

The OAX4010 can be utilized for a wide range of automotive imaging applications, including rear-view cameras, e-mirrors and SVS. Its ability to provide LFM and HDR at high temperatures is important because applications like e-mirrors are often running continuously in extreme temperature conditions. The OAX4010 also enables the emerging AR camera systems to overlay real-time

images on GPS navigation displays, which requires LED traffic signs and signals to be flicker-free. Additionally, this new ISP is pin-to-pin compatible with OmniVision's previous generation ISPs, providing an easy migration path to improved LFM and HDR performance with faster time to market. The OAX4010's combination of the industry's leading LFM and HDR also allows Tier-1 automotive manufacturers to design one camera that can be used in both SVS and e-mirrors. This creates greater economies of scale as a single camera platform can be deployed in multiple CMS applications.

The OAX4010 has an advanced set of safety mechanisms to enable advanced ASIL camera systems and was developed under the ISO26262 compliant process. This image sensor is AEC-Q100 Grade 2 certified and ASPICE CL-2 for automotive applications. Samples are available now.

Find out more at www.ovt.com.



OmniVision


Applications

- Rear View Camera (RVC)
- E-Mirror
- Surround View System (SVS)
- Driver Monitoring System (DMS)

Product Features

- up to 2 megapixel sensor (1920x1080 or 1824x940) @ 60 fps with MIPI output and up to 60 fps with DVP output (3.3V I/O, 16-bit/24-bit mode)
- supports two sensor input through two 2-lane MIPI interfaces or one 4-lane MIPI interface
- supports one sensor input through 4/2/1-lane MIPI interface
- supports two 2-lane MIPI-TX interfaces to output video stream
- supports 4-lane MIPI-TX interface to output video stream
- advanced HALE combination algorithm
- local and global tone mapping support
- automatic white balance (AWB), automatic exposure control (AEC) / automatic gain control (AGC), 50/60 Hz auto flicker detection and elimination
- statistics data of up to four user programmable ROIs
- distortion correction (DC) up to 180° HFOV
- four independent overlay layers and line/arc layers, 32 color/palette per image, line and global transparency control for each layer
- embedded information, including frame counter, temperature, and register data, for each image to enable critical automotive safety applications
- up to eight GPIOs
- 1K bits of one-time programmable memory (OTP)
- brown-out detection circuit and output flag
- JTAG boundary scan
- serial camera control bus (SCCB) master/slave interface for sensor and ASIC configuration
- up to four-wire SPI flash interface to retrieve stored firmware and data from external SPI flash memory
- on-chip DCDC from 1.8V to 1.1V

OAX4010




Ordering Information

- OAX4010-B69G-1A-Z (lead-free) 169-pin BGA, packed in tray
- OAX4010-B69G-TA-Z (lead-free) 169-pin BGA, packed in tape and reel

Product Specifications

- **temperature range:** - operating: -40°C to +105°C ambient temperature
- **input interface:** MIPI RX (1x 4-lane or 2x 2-lane, 1.2 Gbps/lane) or DVP (12-bit, up to 100 MHz)
- **input data format:** 3x12-bit RAW, 3x10-bit RAW, 2x12-bit PWL RAW
- **input clock:** 6 - 36 MHz
- **output interface:** DVP (up to 24-bit, 150 MHz with 3.3V I/O, 100 MHz with 1.8V I/O), MIPI TX (1x 4-lane or 2x 2-lane, 1.2 Gbps/lane)
- **output data format:** YUV422 8/10/12-bit, RGB888 24-bit, RGB565 16-bit, BT1120 16-bit, BT656 8-bit
- **package dimensions:** 7 mm x 7 mm (0.5 mm pitch)

Functional Block Diagram



4275 Burton Drive
Santa Clara, CA 95054
USA

Tel: + 1 408 567 3000
Fax: + 1 408 567 3001
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision and the OmniVision logo are registered trademarks of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision