



# OCOVA vGA product brief



## OmniVision Expands Industry's Smallest BSI Global Shutter Pixel Family with Wafer-Level Camera Module



available in a lead-free package

OmniVision's OCOVA wafer-level camera module is the first CameraCubeChip™ module with Nyxel® technology and features the industry's smallest pixel size of 2.2 microns. The OCOVA expands our family of the industry's smallest GS imagers by providing a VGA resolution option with the best NIR performance in a global shutter device. Existing VGA global shutter devices have low near-infrared (NIR) quantum efficiency (QE) and high modulation transfer function (MTF) degradation, which requires a stronger light source with high power consumption and low performance. The OCOVA features OmniVision's PureCel™Plus-S stacked pixel architecture and Nyxel® NIR technology to enable optimal performance and precision along with industry-leading QE and excellent MTF for sharp, accurate images in machine vision and 3D sensing applications.

The OCOVA is ideal for a wide range of consumer and industrial machine vision and 3D sensing applications that need a global shutter to avoid motion blur, along with top NIR performance that reduces system power consumption by requiring less IR LED illumination in low- and no-light conditions. It combines image sensor OGOVA with image signal processing and optics into a compact wafer-level camera module.

The wafer level module's low light sensitivity is excellent, with significantly lower gain than the industry's typical 3.0 micron pixel size for an improved signal-to-noise ratio. Target applications include facial authentication and eye tracking in smartphones and notebooks, as well as imaging for AR/VR headsets, drones and robots.

The OCOVA's high MTF enables sharper images with greater contrast and more detail, which helps to enhance machine vision decision-making processes. Additionally it features a high QE of 40% at 940 nm and 60% at 850 nm. This industry-leading QE enables devices to see farther and better in low- and no-light conditions, which allows designers to use less IR LED light and achieve lower system-level power consumption. For AR/VR headsets, this reduces heat generation, while industrial and robotics applications can use fewer IR LEDs for lower system cost, or use the same number to achieve a greater image detection range.

Find out more at [www.ovt.com](http://www.ovt.com).



## Applications

- Machine Vision
- Industrial Automation
- Augmented and Virtual Reality
- Gaming
- Biometric Authentication
- Drones
- 3D Imaging
- Industrial Bar Code Scanning

## Product Features

- 2.2  $\mu\text{m}$  x 2.2  $\mu\text{m}$  pixel with PureCel<sup>®</sup>Plus-S Global Shutter and Nyxel<sup>®</sup> technology
- automatic black level calibration (ABLC)
- programmable controls for:
  - frame rate
  - mirror and flip
  - cropping
- support output formats: 10-bit RAW RGB
- fast mode switching
- supports horizontal and vertical 2:1 subsampling
- supports 2x2 binning
- 1-lane MIPI/LVDS serial output interface
- support for image sizes:
  - 640 x 480
  - 320 x 240
- embedded 128 bytes of one-time programmable (OTP) memory for part identification
- two on-chip phase lock loops (PLLs)
- built-in strobe control
- support for multi-sensor mode operation

# OCOVA




## Ordering Information

- OCOVA1B-RAOA-Z (b&w, lead-free) CameraCubeChip<sup>™</sup> with black coating

## Technical Specifications

- active array size: 640 x 480
- maximum image transfer rate:
  - VGA (640x480): 240 fps
  - QVGA (320x240): 480 fps
- power supply:
  - analog: 2.6V (nominal)
  - core: 1.2V (nominal)
  - I/O: 1.8V (nominal)
- power requirements:
  - active: 123 mW
  - XSHUTDN: 10  $\mu\text{A}$
- output interface: 1-lane MIPI/LVDS serial output
- temperature range:
  - operating: -30°C to +85°C junction temperature
  - stable image: 0°C to +60°C junction temperature
- output formats: 10-bit RAW RGB
- lens size: 1/10"
- diagonal field of view (FOV): 89°  $\pm$ 5°
- f no.: 2.2
- focal length: 1.09 mm
- pixel size: 2.2  $\mu\text{m}$  x 2.2  $\mu\text{m}$
- image area: 1443.2  $\mu\text{m}$  x 1091.2  $\mu\text{m}$

## Functional Block Diagram



4275 Burton Drive  
Santa Clara, CA 95054  
USA

Tel: +1 408 567 3000  
Fax: +1 408 567 3001  
www.ovt.com

OmniVision reserves the right to make changes to their products or to discontinue any product or service without further notice. OmniVision, the OmniVision logo, PureCel and Nyxel are registered trademarks of OmniVision Technologies, Inc. CameraCubeChip is a trademark of OmniVision Technologies, Inc. All other trademarks are the property of their respective owners.



OmniVision