

WL2836D

Low noise, High PSRR, High speed, CMOS LDO

[Http://www.ovt.com](http://www.ovt.com)

Descriptions

The WL2836D series is a high accuracy, low noise, high speed, high PSRR, low dropout CMOS Linear regulator with high ripple rejection. The devices offer a new level of cost effective performance in cellular phones, laptop and notebook computers, and other portable devices.

The WL2836D has the fold-back maximum output current which depends on the output voltage. So the current limit functions both as a short circuit protection and as an output current limiter.

The WL2836D regulators are available in standard DFN1x1-4L Package. Standard products are Pb-free and Halogen-free.

Features


- Input Voltage Range : 1.4V~5.5V
- Output Voltage Range : 0.9V~3.3V
- Output current : 300mA
- Quiescent current : 50μA Typ.
- Shut-down current : < 1μA
- Dropout voltage : 140mV @ $I_{OUT}=0.3A$
- PSRR : 78dB @ 1kHz, $V_{OUT}=1.8V$
- Low Output Voltage Noise : $13 \times V_{OUT} \mu V_{RMS}$
- Output Voltage Tolerance : $\pm 1\%$ @ $V_{OUT}>2V$
- Recommend capacitor : 1μF
- Thermal-Overload and Short-Circuit Protection

Applications


- MP3/MP4 Players
- Cellphones, radiophone, digital cameras
- Bluetooth, wireless handsets
- Others portable electronics device



DFN1x1-4L



Pin Configuration (Top View)



I : Device Code

*** : Voltage Code**

Y : Year Code

W: Week Code


For detail marking information, please see page 14.

Marking

Order Information

For detail order information, please see page 14.

Typical Application




Pin Description

DFN1x1-4L

PIN	Symbol	Description
1	V _{OUT}	Output
2	GND	Ground
3	EN	Enable (Active high)
4	V _{IN}	Input
EP		GND level, this pin must connect to GND.

Block Diagram



Absolute Maximum Ratings

Parameter	Value	Unit
Power Dissipation, $P_D @ T_A = 25^\circ\text{C}$	400	mW
V_{IN} Range	-0.3~6.5	V
V_{EN} Range	-0.3~ V_{IN}	V
V_{OUT} Range	-0.3~ V_{IN}	V
I_{OUT}	Internally Limited	
Lead Temperature Range	260	$^\circ\text{C}$
Storage Temperature Range	-55 ~ 150	$^\circ\text{C}$
Operating Junction Temperature Range	150	$^\circ\text{C}$
MSL	Level-1	
ESD Ratings	HBM	7500 V
	MM	300 V

Recommend Operating Ratings

Parameter	Value	Unit
Operating Supply voltage	1.4~5.5	V
Operating Temperature Range	-40~85	$^\circ\text{C}$
Thermal Resistance, $R_{\theta JA}$ (DFN1x1-4L)	250	$^\circ\text{C/W}$



Electronics Characteristics

(Ta=25°C, V_{IN}=V_{OUT}+1V, C_{IN}=C_{OUT}=1 μ F, I_{OUT}=1mA, unless otherwise noted)



Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Output Voltage	V _{OUT}	V _{OUT} ≤ 2V	-20	V _{OUT}	+20	mV
		V _{OUT} > 2V	0.99× V _{OUT}	V _{OUT}	1.01× V _{OUT}	V
Input Voltage	V _{IN}		1.4		5.5	V
Current Limit	I _{LIM}	V _{EN} =V _{IN}	300			mA
Dropout Voltage	V _{DROP}	V _{OUT} =3.3V, I _{OUT} =300mA		118	185	mV
		V _{OUT} =3V, I _{OUT} =300mA		122	192	
		V _{OUT} =2.8V, I _{OUT} =300mA		130	204	
		V _{OUT} =2.5V, I _{OUT} =300mA		140	220	
		V _{OUT} =1.6V, I _{OUT} =300mA		205	320	
		V _{OUT} =1V, I _{OUT} =300mA		370	555	
Line Regulation	ΔV _{LINE}	V _{IN} =V _{OUT} +0.5V~5.5V		1	5	mV
Load Regulation	ΔV _{Load}	I _{OUT} =1~300mA		15	28	mV
Quiescent Current	I _Q	V _{OUT} =2.8V, I _{OUT} =0		50	90	μA
Short Current	I _{SHORT}	V _{EN} =V _{IN} , V _{OUT} Short to GND		120		mA
Shut-down Current	I _{SHDN}	V _{EN} =0V			1.0	μA
Power Supply Rejection Rate	PSRR	V _{IN} =(V _{OUT} +1V) _{DC} + 0.5V _{P-P} I _{OUT} =10mA, V _{OSET} =1.8V	f=100Hz	80		dB
			f=1kHz	78		dB
			f=10kHz	65		dB
			f=100kHz	56		dB
			f=1MHz	43		dB
EN logic high voltage	V _{ENH}	V _{IN} =5.5V, I _{OUT} =1mA	1			V
EN logic low voltage	V _{ENL}	V _{IN} =5.5V, V _{OUT} =0V			0.4	V
EN Input Current	I _{EN}	V _{EN} = 0 to 5.5V		120		nA
Output Noise Voltage	e _{NO}	10Hz to 100KHz, C _{OUT} =1μF		13× V _{OUT}		μV _{RMS}
Thermal shutdown threshold	T _{SD}			160		°C
Thermal shutdown hysteresis	Δ T _{SD}			30		°C
Auto-discharge Nch Tr, ON Resistance	R _{LOW}	V _{IN} =4V, V _{CE} =0V, V _{OUT} =2.8V		120		Ω

Typical characteristics ($T_a=25^{\circ}\text{C}$, $V_{\text{IN}}=V_{\text{OUT}}+1\text{V}$, $I_{\text{OUT}}=1\text{mA}$, $C_{\text{IN}}=C_{\text{OUT}}=1\ \mu\text{F}$, unless otherwise noted)



$V_{\text{OUT}}=1.2\text{V}$





$V_{\text{OUT}}=1.8\text{V}$




$V_{\text{OUT}}=2.8\text{V}$




V_{OUT}=1.8V




V_{OUT}=1.8V




V_{OUT}=2.8V




V_{OUT}=3.0V




V_{OUT}=3.3V




V_{out}=1.2V





V_{out}=1.8V





V_{out}=2.8V





V_{out}=1.05V



V_{OUT}=1.8V




V_{OUT}=2.8V




1.Start up (Soft Start from EN)

$V_{OUT}=1.2V$

$V_{IN}=2.2V, C_{OUT}=1\mu F, I_{OUT}=10mA$




$V_{IN}=2.2V, C_{OUT}=1\mu F, I_{OUT}=250mA$




$V_{OUT}=1.8V$

$V_{IN}=2.8V, C_{OUT}=1\mu F, I_{OUT}=10mA$




$V_{IN}=2.8V, C_{OUT}=1\mu F, I_{OUT}=300mA$




$V_{OUT}=2.8V$

$V_{IN}=3.8V, C_{OUT}=1\mu F, I_{OUT}=10mA$




$V_{IN}=3.8V, C_{OUT}=1\mu F, I_{OUT}=300mA$




2.Shutdown (Shutdown from EN)

$V_{OUT}=1.2V$

$V_{IN}=2.2V, C_{OUT}=1\mu F, I_{OUT}=10mA$




$V_{IN}=2.2V, C_{OUT}=1\mu F, I_{OUT}=300mA$




$V_{OUT}=1.8V$

$V_{IN}=2.8V, C_{OUT}=1\mu F, I_{OUT}=10mA$




$V_{IN}=2.8V, C_{OUT}=1\mu F, I_{OUT}=300mA$




$V_{OUT}=2.8V$

$V_{IN}=3.8V, C_{OUT}=1\mu F, I_{OUT}=10mA$



$V_{IN}=3.8V, C_{OUT}=1\mu F, I_{OUT}=300mA$




3. Load & Line Transient

Load step


$V_{OUT}=1.2V$

$V_{IN}=2.2V, C_{OUT}=1\mu F, I_{OUT}=1mA-200mA$ in $1\mu s$




Line Step

$V_{IN}=2.2V-3.2V$ in $20\mu s, C_{OUT}=1\mu F, I_{OUT}=1mA$




$V_{OUT}=1.8V$

$V_{IN}=2.8V, C_{OUT}=1\mu F, I_{OUT}=1mA-300mA$ in $1\mu s$




$V_{IN}=2.8V-3.8V$ in $20\mu s, C_{OUT}=1\mu F, I_{OUT}=1mA$




$V_{OUT}=2.8V$

$V_{IN}=3.8V, C_{OUT}=1\mu F, I_{OUT}=1mA-300mA$ in $1\mu s$




$V_{IN}=3.8V-4.8V$ in $20\mu s, C_{OUT}=1\mu F, I_{OUT}=1mA$




PACKAGE OUTLINE DIMENSIONS


DFN1x1-4L





TOP VIEW



BOTTOM VIEW



SIDE VIEW




RECOMMENDED LAND PATTERN (Unit:mm)


Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.32	0.37	0.42
A1	-	-	0.05
A3	0.10 Ref.		
b	0.17	0.22	0.28
L	0.17	-	0.30
D	0.95	1.00	1.05
E	0.95	1.00	1.05
D1	0.43	0.48	0.54
E1	0.43	0.48	0.54
K	0.14	-	-
e	0.65BSC		

TAPE AND REEL INFORMATION


Reel Dimensions



Tape Dimensions



Quadrant Assignments For PIN1 Orientation In Tape



RD	Reel Dimension	☒ 7inch	☐ 13inch
W	Overall width of the carrier tape	☒ 8mm	☐ 12mm ☐ 16mm
P1	Pitch between successive cavity centers	☒ 2mm	☐ 4mm ☐ 8mm
Pin1	Pin1 Quadrant	☒ Q1	☐ Q2 ☐ Q3 ☐ Q4

ORDER INFORMATION

Ordering No.	Vout (V)	Package	Operating Temperature	Marking	Shipping
WL2836D08-4/TR	0.8	DFN1x1-4L	-40~+85°C	Ih YW	Tape and Reel, 10000
WL2836D09-4/TR	0.9	DFN1x1-4L	-40~+85°C	IA YW	Tape and Reel, 10000
WL2836D10-4/TR	1.0	DFN1x1-4L	-40~+85°C	IB YW	Tape and Reel, 10000
WL2836D105-4/TR	1.05	DFN1x1-4L	-40~+85°C	IC YW	Tape and Reel, 10000
WL2836D11-4/TR	1.1	DFN1x1-4L	-40~+85°C	ID YW	Tape and Reel, 10000
WL2836D12-4/TR	1.2	DFN1x1-4L	-40~+85°C	IE YW	Tape and Reel, 10000
WL2836D15-4/TR	1.5	DFN1x1-4L	-40~+85°C	IG YW	Tape and Reel, 10000
WL2836D18-4/TR	1.8	DFN1x1-4L	-40~+85°C	IH YW	Tape and Reel, 10000
WL2836D25-4/TR	2.5	DFN1x1-4L	-40~+85°C	IK YW	Tape and Reel, 10000
WL2836D27-4/TR	2.7	DFN1x1-4L	-40~+85°C	IY YW	Tape and Reel, 10000
WL2836D28-4/TR	2.8	DFN1x1-4L	-40~+85°C	IL YW	Tape and Reel, 10000
WL2836D29-4/TR	2.9	DFN1x1-4L	-40~+85°C	Ig YW	Tape and Reel, 10000
WL2836D30-4/TR	3.0	DFN1x1-4L	-40~+85°C	IM YW	Tape and Reel, 10000
WL2836D33-4/TR	3.3	DFN1x1-4L	-40~+85°C	IN YW	Tape and Reel, 10000