



OV2732

1080p product brief



Low-Power 1080p High Definition PureCel® Sensor for Security Applications

OMNIVISION's OV2732 is a compact and power-efficient PureCel® image sensor designed for IoT-based residential and commercial monitoring systems. The OV2732 captures quality images and videos with staggered high dynamic range (HDR), ensuring excellent scene reproduction in all lighting environments. The sensor features frame sync for use in multi-camera or 360-degree camera systems and supports ultra-low power mode (ULPM) and an ambient light sensor (ALS), making it particularly well-suited for battery-powered security applications.

Built on OMNIVISION's PureCel® technology, the 1/4-inch OV2732 captures 1080p high definition (HD) video at 60 frames per second (fps), 720p HD video at 90 fps, and VGA resolution video at 120 fps. The OV2732 delivers crisp images and video, even in challenging low-light conditions.

Find out more at www.ovt.com.



- OV2732-H46A-1E (color, lead-free)
46-pin CSP

Applications

- Internet of Things (IoT)
- high-end video conferencing
- security
- lifestyle cameras
- home monitoring

Technical Specifications

- active array size:** 1920 x 1080
- maximum image transfer rate:**
 - 1080p: 60 fps
 - 720p: 90 fps
 - VGA: 120 fps
 - QVGA: 240 fps
- power supply:**
 - core: 1.2V
 - analog: 2.8V
 - I/O: 1.8V
- power requirements:**
 - active: 110 mW
- output interfaces:**
 - two-lane MIPI / DVP parallel
- temperature range:**
 - operating: -40°C to +85°C junction temperature
 - stable image: 0°C to +60°C junction temperature
- output formats:** 10/12-bit RAW RGB
- lens size:** 1/4"
- lens chief ray angle:** 12° linear
- scan mode:** progressive
- shutter:** rolling shutter
- pixel size:** 2 μm x 2 μm
- 3868 μm x 2190 μm

Product Features

- programmable controls:**
 - gain
 - exposure
 - frame rate
 - image size
 - horizontal mirror
 - vertical flip
 - cropping
 - windowing
- automatic image control functions:**
 - black level calibration (BLC)
- serial camera control bus (SCCB)**
- defective pixel correction (DPC)**
- digital video port (DVP) parallel output interface**
- support for two lane MIPI interface (up to 800 Mbps)**
- support for image sizes:**
 - 1080p @ 60 fps
 - 720p @ 90 fps
 - VGA @ 120 fps
 - QVGA @ 240 fps, and more
- support for light sensing mode (LSM)**
- support for staggered 2 frame HDR**
- support for black sun cancellation**
- on-chip phase lock loop (PLL)**

Functional Block Diagram

