



OH02A10

2-Megapixel Product Brief



Best-in-Class Image Quality and High Frame Rate 1080p High Definition Video Capture for Endoscopic Applications

OMNIVISION's OH02A10 CMOS image sensor leverages 1.4-micron PureCel® pixel architecture to deliver best-in-class image quality and high frame rate in full 1080p high definition (HD) video to endoscopic applications, such as urology, laparoscopy, gynecology, cardiology and surgery.

By using PureCel® pixel architecture, the OH02A10 offers the highest-quality imaging capabilities with improved sensitivity and quantum efficiency, high full-well capacity, low color crosstalk, and minimal blooming and noise. The OH02A10's broadband double anti-reflective coating reduces flare in the visible and near-infrared spectrums, which is typically caused by strong ancillary illumination during surgical operations.

The compact OH02A10 is capable of recording full 1080p HD video at 60 frames per second (fps) or 720p HD video at 90 fps to ensure clear scene

reproduction with minimal motion artifacts. The sensor supports interlaced high dynamic range (HDR), which enables clear image capture with less saturation and excellent low light sensitivity in difficult high and low lighting situations. The OH02A10 is also stereo-ready with frame synchronization for 3D surgical applications.

OMNIVISION's OH02A10 consumes just 90 mW when recording 1080p HD video at 60 fps, which helps reduce heat generation at the distal tip of the endoscope to improve patient comfort and simplify design.

The OH02A10 is available in a 1/6-inch optical format and a compact 3.8 mm x 2.9 mm chip scale package (CSP). This sensor can be autoclaved and sterilized for reusable and single-use applications respectively.

Applications

- Medical endoscopes
- Veterinarian endoscopes
- Dental equipment
- Industrial endoscopes

Features

- **Active array size:** 1920 x 1080
- **Maximum image transfer rate:**
 - 1920 x 1080: 60 fps
 - 1280 x 720: 90 fps
- **Power supply:**
 - Core: 1.2V
 - Analog: 2.8V
 - I/O: 1.8V
- **Output interfaces:**
Up to 2-lane MIPI serial output interface
- **Output formats:** 10-bit RGB RAW
- **Lens size:** 1/6"
- **Pixel size:** 1.4 μm x 1.4 μm

Version 1.7, August 2026