



OHOTA

400 x 400 Product Brief



Medical Image Sensor for Endoscopes and Catheters Improves Image Quality and Reduces Power Consumption

OMNIVISION's OHOTA is an OVMed® medical grade CMOS image sensor with a package size of just 0.55 mm x 0.55 mm, featuring a 1.0-micron pixel and a 1/31.567-inch optical format. The OHOTA takes medical visualization to the next level by quadrupling the RGB image resolution of its predecessor to 400 x 400, or 160 Kpixels, at 30 frames per second, while reducing the power consumption by 20% to 20 mW. This allows designers to add ultra-compact visualization to single-use and reusable endoscopes, as well as catheters and guidewires, with a small outer diameter of 1-2 mm.

The OHOTA's increased resolution improves the visualization of tissues and other fine details inside the human body, allowing surgeons to see crisper images during procedures such as neuro, ophthalmic, ENT, cardiac, spinal, urology, gynecology and arthroscopy, as well as dental and veterinary diagnosis and surgery. Additionally, the sensor's lower power consumption reduces "chip on tip" camera heat for greater patient comfort and longer procedure durations, while reducing noise.

To achieve this increase in resolution, along with a smaller pixel size and optical format, the OHOTA is built on OMNIVISION's PureCel®Plus-S stacked die technology. This next-generation pixel technology also provides higher color fidelity and excellent low light sensitivity of 3600 mV/lux-sec, along with a high signal-to-noise ratio of 37.5 dB for greater image quality. Additionally, PureCel®Plus-S enables the OHOTA's higher full well capacity (FWC), zero blooming and lower power consumption, resulting in better patient outcomes.

Other key features include a 15.5-degree chief ray angle, enabling the use of lenses with high fields of view and short focus distances. It also supports a 4-wire interface, as well as RAW analog data output, both of which can transmit via cables as long as 4 meters with minimal signal noise. The OHOTA sensor also interfaces with OMNIVISION's existing OV426 analog-to-digital-conversion bridge chip for backward compatibility and easy adoption.

Additionally, the OHOTA is autoclavable for reusable endoscope sterilization.

Applications

- Medical endoscopes
- Medical and dental equipment
- Catheters
- Robotic surgery
- Guidewires

Features

- **Active array size:** 400 x 400
- **Maximum image transfer rate:**
 - 400 x 400: 30 fps
- **Power supply:**
 - Analog: 3.3V ±5%
- **Output interfaces:** AntLinx® analog output
- **Output formats:** analog signal output
- **Lens size:** 1/31.567"
- **Pixel size:** 1.008 µm x 1.008 µm

Version 1.2, August 2026